Terra: Scalable Cross-Layer GDA Optimizations

Jie You

University of Michigan Ann Arbor, Michigan jieyou@umich.edu

Abstract

Geo-distributed analytics (GDA) frameworks transfer large datasets over the wide-area network (WAN). Yet existing frameworks often ignore the WAN topology. This disconnect between WAN-bound applications and the WAN itself results in missed opportunities for cross-layer optimizations.

In this paper, we present Terra to bridge this gap. Instead of decoupled WAN routing and GDA transfer scheduling, Terra applies scalable cross-layer optimizations to minimize WAN transfer times for GDA jobs. We present a two-pronged approach: (i) a scalable algorithm for joint routing and scheduling to make fast decisions; and (ii) a scalable, overlay-based enforcement mechanism that avoids expensive switch rule updates in the WAN. Together, they enable Terra to quickly react to WAN uncertainties such as large bandwidth fluctuations and failures in an application-aware manner as well.

Integration with the FloodLight SDN controller and Apache YARN, and evaluation on 4 workloads and 3 WAN topologies show that Terra improves the average completion times of GDA jobs by $1.55 \times -3.43 \times$. GDA jobs running with Terra meets $2.82 \times -4.29 \times$ more deadlines and can quickly react to WAN-level events in an application-aware manner.

1 Introduction

To cope with the increasing number of Internet users and edge devices [11], large organizations leverage tens to hundreds of datacenters and edge sites [1, 10, 12, 28] to gather data related to end-user sessions and their devices as well as monitoring logs and performance counters. Analyzing and personalizing this data can provide tremendous value in improving user experience [8, 65, 72]. Consequently, a growing body of recent work has focused on enabling geo-distributed analytics (GDA), i.e., executing computation tasks on the data stored in-place at different sites instead of copying to a single datacenter. Faster completions of these jobs can enable log processing [65, 66], SQL query processing [71, 72], and machine learning [48] over large geo-distributed datasets. Assuming static WAN bandwidth, existing solutions optimize query planning [49, 66, 71, 72], scheduling [50, 65], and algorithm design [48] to reduce inter-datacenter transfers over the WAN. This is because WAN bandwidth is expensive [54, 58] and often a major performance bottleneck for these communication-intensive jobs [48, 71, 72] (e.g., due to large intermediate data transfers [65]).

Unfortunately, existing GDA frameworks ignore the WAN topology and treat the WAN as a full mesh or a non-blocking

Mosharaf Chowdhury University of Michigan Ann Arbor, Michigan mosharaf@umich.edu

switch [48, 50, 65, 66, 71, 72]. Although these simplifications – end-to-end tunnels and independent links, respectively – decouple GDA systems from WAN traffic engineering, they introduce a disconnect. Applications cannot optimize on actual points of contention which are hidden and constantly changing in the WAN; at the same time, WAN traffic engineering cannot optimize application-level objectives.

This mismatch between application- and WAN-level goals prolongs the communication stages of GDA jobs and increases their job completion times (JCT) (§2). Existing solutions that attempt to align the two [61, 83] do not scale to large WAN topologies or complex jobs, and they themselves can become the bottleneck (§3). The presence of WAN uncertainties such as large bandwidth fluctuates and link failures adds to the challenge because GDA jobs cannot rapidly adapt to changing WAN conditions.

Our goal in this paper is to speed up the communication stages of GDA jobs and to make them more robust to WAN uncertainties. To this end, we present Terra, a scalable framework that bridges the gap between GDA frameworks and the WAN by co-optimizing application-level transfer scheduling and WAN-level routing decisions. Terra's design is guided by two high-level observations:

- Redundant paths in the WAN topology should be fully utilized in order to minimize GDA transfer times; and
- SD-WAN rule updates are expensive and should be avoided whenever possible for fast decision enforcement.

We propose a two-pronged approach that can scale to large GDA jobs and WAN topologies while adhering to these observations. First, we propose a scalable algorithm to quickly compute multipath WAN routing and GDA scheduling decisions (§3). To this end, we generalize existing coflow-based solutions used inside single datacenters [30, 33, 83] to consider the WAN topology. Then we make it scalable by treating all flows between the same datacenter pair from the same coflow together instead of treating each one independently, reducing the problem size by many orders-of-magnitude. Second, we propose a multipath overlay on top of single-path TCP connections over the entire WAN and enforce our algorithmdetermined routes, schedules, and rates on this overlay, limiting the need for WAN rule updates only to (re)initialization (§4). Our algorithm-systems co-design can address WAN uncertainties by quickly recomputing GDA transfer schedules and reconfiguring the WAN overlay.

We have a full-stack implementation of the proposed solution (§5), integrated with the FloodLight [13] SDN controller



Figure 1. Opportunities for scheduling-routing co-optimization of two jobs running across three datacenters. (a) MapReduce Job running on WAN topology. (b) Coflows from Job-1 (dark/blue) has 1 flow and Job-2 (light/orange) has 2 flows (dark/red and light/orange). (c)–(f) Bandwidth allocations of the two bottleneck links ($A \rightarrow B$ and $C \rightarrow B$) w.r.t. time for 4 different scheduling-routing policies. Average completion times for (c) per-flow fair sharing is 14 seconds; (d) multipath is 10.6 seconds; (e) intra-datacenter coflow scheduling [33, 83] is 12 seconds; (f) Terra finds the optimal routing-scheduling joint solution: 7.15 seconds.

in the network-side and Apache YARN [3] in the applicationside. It provides a simple API to express WAN coflows. Userwritten jobs in a framework remain unmodified.

We evaluated Terra using three WAN topologies (Microsoft's SWAN [47], Google's G-Scale [53], and AT&T's MPLS topology [6]) and four different workloads (BigBench [7], TPC-DS [15], and TPC-H [16] with complex DAGs and Facebook data transfer matrices from simple MapReduce jobs [9, 14] (§6). For the small-scale testbed experiment using the SWAN topology, Terra improved the average job completion time (JCT) by $1.55 \times -3.43 \times$ on average and $2.12 \times -8.49 \times$ at the 95th percentile, while improving WAN utilization by 1.32×-1.76×. For large-scale simulations, Terra improved the average JCT by $1.04 \times -2.53 \times$ for the smallest topology (SWAN) and $1.52 \times -26.97 \times$ for the largest topology (AT&T) against baselines such as per-flow fairness, multipath routing, SWAN-MCF [47], Varys [33], and Rapier [83]. Terra can complete 2.82×-4.29× more coflows within their deadlines. We also show that it can react quickly to WAN events, it can scale well, and its benefits hold across a wide range of parameter and environment settings.

In summary, our contributions in this paper are three-fold:

- 1. Identifying scalability bottlenecks in the GDA-WAN cooptimization problem both from algorithm and system design perspectives.
- 2. A scalable algorithm that co-optimizes complex GDA jobs with large WAN topologies to minimize their data transmission times.
- A scalable system design and implementation that integrates with GDA frameworks and SD-WANs to enforce those decisions and provides large performance benefits.

2 Background and Motivation

This section provides a quick overview of GDA systems (§2.1), common WAN models used by them (§2.2), and the coflow abstraction (§2.3), followed by an illustration of the advantages of application-WAN co-optimization (§2.4).

2.1 Geo-Distributed Analytics (GDA)

GDA users submit jobs written in higher-level interfaces – e.g., in SparkSQL [26], Hive [4], or GraphX [41] – typically to one central *job master* that resides in one of the many distributed sites/datacenters [65, 72]. The master constructs an optimized execution plan [71] for the job and represents it as a directed acyclic graph (DAG). Nodes of this DAG represent computation stages with many parallel tasks and edges represent stage dependencies as well as WAN transfers between tasks in different datacenters. A centralized scheduler then places these tasks at machines across different datacenters based on data locality, resource availability, and their dependencies [50, 71, 72]. The durations of these jobs typically range from minutes to tens of minutes and communication across the WAN is often the bottleneck [65, 71].

2.2 Inter-Datacenter WAN Model

Datacenters used by GDA frameworks are connected by a WAN. While such WANs have traditionally been optimized using MPLS-based [75] traffic engineering, centralized SD-WANs are becoming more popular [47, 53, 58]. We assume the latter, which enables Terra to make and enforce topology-aware routing decisions. Existing GDA systems assume either a full mesh with heterogeneous link capacities [48, 71] or a non-blocking switch with contentions only at the uplinks or downlinks of each datacenter [65]. As such, they miss the



Figure 2. Need for application-aware WAN re-optimization. (a) On Figure 1a's topology, Coflow-3 (dark/blue) has 1 flow and Coflow-4 (light/orange) has 2 flows (dark/red and light/orange). Average completion times (b) for the optimal solution is 8 seconds; (c) after rerouting f_{42} due to the failure of the A–C link is 18 seconds; (d) for the new optimal solution after the failure is 14 seconds.

opportunity to utilize redundant paths in WAN.

Existing solutions assume that the WAN topology and available bandwidth remain fixed during a job's execution. However, this may lead to performance issues when WAN configuration is updated in the middle of a job's execution. For example, SWAN [47] updates WAN configurations every 5 minutes. Because Terra is integrated with the SD-WAN controller, unlike existing solutions, it can monitor and react to these changes. High-priority, user-facing, and deadlinesensitive traffic are prioritized by WAN managers [57, 58], including Terra. So we consider a link's bandwidth to be the remaining capacity excluding those traffic.

2.3 The Coflow Abstraction

GDA jobs typically use the same programming models (e.g., MapReduce) as traditional analytics jobs running within a single datacenter [65, 71, 72]. These programming models often have a communication stages between computation stages, where the computation stage cannot start until all flows in the preceding communication stage have finished. Recently, Chowdhury and Stoica defined such a collection of flows with a shared fate as a coflow [30], and many have shown that minimizing a coflow's completion time (CCT) can decrease a job's completion time [18, 33, 83]. The coflow abstraction generalizes intermediate data transfers (i.e., shuffles) for GDA jobs too [62].

2.4 Potential Benefit of Co-Optimization

Setup Without loss of generality, we consider a GDA job with one map stage and one reduce stage for ease of explanation. Now consider this job running on the WAN topology with 3 datacenters $\{A, B, C\}$ as shown in Figure 1a. Suppose a GDA query planning and task placement algorithm [49, 66, 71, 72] has put some map tasks in *A*, others in *B*, and all reduce tasks in *B*. Therefore, part of its shuffle traffic would be transfered over the WAN from *A* to *B*, while the other part would be inside datacenter *B*. We focus on WAN traffic here because the limited bandwidth of WAN becomes the bottleneck for GDA jobs [65, 71, 72]. Assuming the total volume of intermediate data generated by M_1 at datacenter *A* to be 5 GB, we can now form a coflow (Coflow-1 in Figure 1b). Coflow-2 is similarly generated, but with a different communication pattern. Our goal now is to minimize the average

completion time for both coflows.

Existing Solutions First, let us consider the classic flow-level fair sharing that equally divides the $A \rightarrow B$ link between flows f_{11} and f_{21} (Figure 1c). Thus, both flows complete by 8 seconds, whereas f_{22} completes by 20 seconds facing no contention. Consequently, Coflow-1 and Coflow-2 complete in 8 and 20 seconds, respectively. The average completion time is 14 seconds.

A simple improvement would be using multiple paths (e.g., MPTCP [36]) to increase network utilization (Figure 1d). In this case, all the flows are split across available paths. Assuming equal split and fair sharing in each link, the average completion time is 10.6 seconds.

Coflow-aware scheduling [31-33, 83] improves the average completion time by considering *all* the flows of the same coflow together. In this case, f_{11} will be scheduled before f_{21} on the *A*–*B* link (Figure 1e). Consequently, Coflow-1 finishes in 4 and Coflow-2 in 20 seconds. The average completion time is 12 seconds. These coflow-based solutions still fall short either by assuming a non-blocking topology [33] or due to considering a single path [83].

Co-Optimization Finds the Optimal Solution So far we have shown 3 sub-optimal solutions, where they only optimize one side of the Application-WAN duo. However, if we consider both simultaneously and combine coflow scheduling with multipath routing together, we can achieve the optimal average completion time of only 7.15 seconds (Figure 1f).

Note that we considered only two jobs and a minimal fullmesh topology in the offline scenario. Terra performs even better with more jobs, on larger WAN topologies that are not full mesh, and in online scenarios (§6).

Re-Optimization is Necessary Under Uncertainties Consider the same topology as in Figure 1a but with two different coflows (Figure 2a). Existing WAN-agnostic solutions [65, 71] will schedule Coflow-3 and Coflow-4 together to achieve the optimal average completion time of 8 seconds. However, if the link between *A* and *C* fails (or experiences a massive increase in high-priority traffic) right after the scheduling decision has been made, the WAN will reroute f_{42} and the completion times of Coflow-3 and Coflow-4 would become 16 and 20 seconds, respectively. Hence, the average completion time would be 18 seconds.

The optimal solution is rescheduling Coflow-3 before

	WAN-	Leverages	App-	Re-
	Aware*	Multipath	Aware	Optimizes†
Per-Flow/TCP	X	X	X	×
Multipath/MPTCP	×	1	×	×
Datacenter Coflows	×	×	1	×
SD-WANs	1	1	×	×
GDA Systems	×	×	1	×
Terra	1	✓	1	\checkmark

 Table 1. Terra vs existing solutions. *WAN-Aware: does not assume full-mesh topology, non-blocking core, or symmetric paths.

 †Re-Optimize: application-aware re-scheduling and rerouting of WAN transfers.

Coflow-4 so that they complete in 8 and 20 seconds for the new minimum average completion time of 14 seconds.

2.5 Summary

Table 1 compares the solutions discussed above across key criteria. The key takeaways from this section are:

- The optimal average coflow completion time can only be achieved when jointly considering routing and scheduling;
- 2. In the presence of WAN uncertainties (e.g., bandwidth fluctuations and failures), application-level scheduling must react to WAN-level routing, and vice versa.

3 Terra: Algorithm Design

Given the benefits of co-optimization, the need for fast reoptimizations, and the scale and heterogeneity of the WAN, we must design a cross-layer solution that can perform well at WAN scale. This requires both designing a scalable algorithmic solution that can quickly make joint scheduling and routing decisions and a scalable system design that can quickly enforce those decisions throughout the WAN. In this section, we focus on the former. Section 4 discusses the latter.

3.1 Minimizing the Average Completion Time

Terra's primary goal is faster completions of WAN transfers from geo-distributed jobs, i.e., *minimizing the average CCT*. Given a coflow, Terra must decide *when to start* individual flows, *at what rate* to send them, and *which path(s)* each flow should take.

This problem is computationally intractable even when all coflows start together, their traffic matrices are known a priori, and the WAN is non-blocking. Because inter-coflow scheduling in a non-blocking datacenter is known to be NP-hard under these assumptions [33], the counterpart on a general WAN topology is NP-hard too. Given the intractability of the problem, we first focus on designing an efficient offline heuristic (§3.1.1–§3.1.2), then extend to online scenarios (§3.1.3).

Consider a WAN graph G = (V, E), where V is the set of nodes – sets of datacenters – and E is the set of WAN links. We represent multiple physical links between u and v ($u, v \in V$) with one logical link $e = (u, v) \in E$ with the cumulative bandwidth. At time T, e's available bandwidth is $c_T(u, w)$. We



Figure 3. Scheduling overhead of a state-of-the-art solution [83].



Figure 4. Scaling down the number of flows in a coflow.

consider the offline problem of scheduling-routing $|\mathbb{C}|$ GDA coflows ($\mathbb{C} = \{C_1, C_2, \dots, C_{|\mathbb{C}|}\}$) that arrived at time *T*.

3.1.1 The Minimum CCT of a Single Coflow

We start by focusing on a single coflow and decide *how to route* its flows and *at what rate* to send the traffic.

Scalability Limitation Calculating the rate and routing for *every* single flow is impractical, because the number of flows for even one coflow can be very large. Per our measurement, the computation time of a state-of-the-art solution that considers coflow routing [83] is 1.952 seconds on average for the BigBench workload on the SWAN topology. The computation overhead only increases for even larger topologies (Figure 3). Clearly, we cannot calculate rate allocation and routing for each flow of each coflow.

Per-Flow Rate Allocation is Unnecessary Existing solutions show minimal coflow completion time can be achieved by enforcing per-flow rate to ensure that *all of its flows finish together* [32, 33, 83]. However, we observe that we can still achieve minimal coflow completion time, even when individual flows do not finish together.

Consider a MapReduce job running on the same WAN provided in Figure 1a. Assume there are 5n map tasks placed in *B*, 3n map tasks placed in *C* and 2 reduce tasks placed in *A* (Figure 4a). So there are a total of 16*n* flows in this coflow. Suppose for each flow we need to send 1 GB data, enforcing *all flows finish together* gives all flows 1/n Gbps throughput. This allocation gives a minimal coflow completion time of 8n seconds, and both link $B \rightarrow A$ and $C \rightarrow A$ are fully utilized all the time.

Now, we take all the flows traversing through link $B \rightarrow A$, and change their rate allocation – we schedule them one-ata-time in the FIFO order, allocating the entire bandwidth of $B \rightarrow A$ (10 Gbps) to each of them. We can still achieve the same CCT of 8*n* seconds. This gives us the following lemma.

Lemma 3.1. If multiple flows of the same coflow have

the same <src datacenter, dst datacenter> pair, all workconserving rate allocation of them will achieve the same completion time.

Consequently, we can group flows within a coflow by their <src_datacenter, dst_datacenter> tuple. The rates of individual flows within such a group do not directly affect the coflow completion time, as long as the total rate of the group remains the same. This grouping is similar to that of Flow-Group [58]; for simplicity, we refer to such groups of flows as FlowGroups.

The notion of FlowGroup brings performance improvements in both calculating and enforcing the rate allocation. Because we only need per-FlowGroup rate allocation, the scale of our problem formulation is reduced to orders-ofmagnitude smaller (O(|FlowGroups|/|Flows|)). For example, in Figure 4b, 16n flows become only 2 FlowGroups. This significantly lowers our scheduling overhead (§6.6).

Solution Approach We can now formulate an optimization problem to minimize the CCT for a single coflow on a general topology. Previous works [83] assumed that a flow can only traverse through a single path, leading to an Integer Linear Programming (ILP) formulation, which is computationintensive. Because of Lemma 3.1, we can assume that a Flow-Group can be split across many paths, therefore eliminating all integral constraints and leading to a LP formulation.

We organize our solution in two steps:

- 1. Scale down by coalescing flows into FlowGroups; and
- 2. Obtain fractional routes for FlowGroups while minimizing the CCT.

Step 1: Scaling Down Using FlowGroups In this step, we collapse all flows from the same coflow with the same <src_datacenter, dst_datacenter> tuple to one FlowGroup. We can now represent a coflow C_i as a collection of Flow-Groups $D_i = [d_i(u, v)]_{|D| \times |D|}$, where $|d_i(u, v)|$ represents the total amount WAN transfers between the machines of C_i in datacenters u and v. \mathbb{D}_i represents the set of FlowGroups with non-zero volumes in D_i .

Step 2: Determining CCT Lower-Bound We now determine the paths and rates of individual FlowGroups to minimize the CCT. We denote the completion time of coflow C_i by Γ_i . Here Γ_i is defined as:

$$\Gamma_i = \max_k T(d_i^k), \quad d_i^k \in \mathbb{D}_i,$$

where d_i^k is the k-th FlowGroup of C_i , and $T(\cdot)$ is the completion time of a FlowGroup. Hence, the slowest FlowGroup $d_i^k \in \mathbb{D}_i$ determines Γ_i . Our objective is given as:

Minimize
$$\Gamma_i$$
 (1)

Let us represent the bandwidth allocation of the k-th Flow-Group in \mathbb{D}_i $(1 \le k \le |\mathbb{D}_i|)$ with size $|d_i^k|$ between nodes u and v by $f^k(u, v)$ where $u, v \in V$. To minimize Γ_i , we generalize WSS [32] and MADD [33] to multiple paths to enforce equal rate of progress for all FlowGroups. For each

Pseudocode 1 Offline Scheduling-Routing

1: procedure ALLOCBANDWIDTH(Coflows C, WAN G)

- 2: Scale down *G* by $(1 - \alpha)$ ▶ Starvation freedom
- 3: $\mathbb{C}_{\text{Failed}} = \emptyset$ Coflows not scheduled in entirety
- for all $C_i \in \mathbb{C}$ do 4:
- Γ_i , \mathbf{f}_i^k = Solve Optimization (1) for C_i on G5:
- if $\Gamma_i = -1$ then 6:
- 7: $\mathbb{C}_{\text{Failed}} = \mathbb{C}_{\text{Failed}} \bigcup C_i$
- 8: continue 9:
 - if $D_i \neq -1$ then
- Scale down \mathbf{f}_i^k by Γ_i/D_i 10:
- 11:
- $\mathbb{P}_{i}^{k} = \{ \text{End-to-end paths from } \mathbf{f}_{i}^{k} \text{ allocations} \}$ $G = \text{Updated } G \text{ by subtracting } \mathbf{f}_{i}^{k} \text{ allocations}$ 12:
- $C^* = \bigcup C$ for all $C \in \mathbb{C}_{Failed}$ 13:
 - ▶ Work conservation Allocate C^* on G using MCF

 $\triangleright C_i$ has a deadline

- 15: Allocate $\mathbb{C} \setminus C^*$ on *G* using MCF
- 16: end procedure

14:

- 17: procedure MINIMIZECCTOFFLINE(Coflows C)
- 18: $\mathbb{C}' = \text{Sort } \mathbb{C} \text{ by increasing } \Gamma_i$
- 19: allocBandwidth(\mathbb{C}', G)
- 20: end procedure

FlowGroup, we can then ensure that they make $1/\Gamma_i$ progress every time unit by enforcing the following constraints:

$$\sum_{w \in V} f^k(\operatorname{src}(d_i^k), w) = |d_i^k| / \Gamma_i$$
$$\sum_{w \in V} f^k(w, \operatorname{dst}(d_i^k)) = |d_i^k| / \Gamma_i$$

The former ensures that the outgoing rate of a FlowGroup is proportional to its volume, while the latter enforces the same on the receiving end. Finally, we enforce usual capacity and flow conservation as follows.

$$\sum_{v \in V} f^{k}(u, v) + f^{k}(v, u) = 0, \quad \forall u \neq \operatorname{src}(d_{i}^{k}), \operatorname{dst}(d_{i}^{k})$$
$$\sum_{v \in V} f^{k}(u, v) \leq c_{T}(u, v)$$
$$f^{k}(u, v) \geq 0$$

Note that enforcing $1/\Gamma_i$ rate to all FlowGroups leaves the maximum amount of bandwidth possible for other coflows that are scheduled after C_i without sacrificing C_i 's CCT. Work conservation uses up any remaining bandwidth (§ 3.1.2).

If Optimization (1) has a feasible solution for C_i , it creates a matrix $\mathbf{f}_i^k = [f^k(u, v)]_{|V| \times |V|}$ for each FlowGroup corresponding to its allocations on individual links of the WAN. Because $f^k(u, v)$ can be non-integers, a FlowGroup can be subdivided across many paths from u to v. We enforce this using an overlay in our systems design (§4).

3.1.2 Scheduling Multiple Coflows

We now move on to considering multiple coflows in the offline scenario. Given multiple coflows, scheduling one coflow

Pseudocode 2 Online Scheduling-Routing

1:	procedure ONAR	RIVAL(Coflows	C, Coflow C_i)
2:	if $D_i \neq -1$ then		$\triangleright C_i$ has a deadline
3:	G' = Scale dow	n G by $(1 - \alpha)$	
4:	$G' = G' - \{\mathbf{f}_i^k\}$	\forall admitted C_j	Guarantee admitted
5:	$\Gamma_i = \text{Solve Opti}$	mization (1) for (C_i on G'
6:	if $\Gamma_i > \eta D_i$ the	n	
7:	Reject C_i	▶ Reject C _i i	f its deadline cannot be met
8:	$\mathbb{C} = \mathbb{C} \bigcup C_i$		
9:	$\mathbb{C}' = \text{Sort } \mathbb{C} \text{ by } d$	ecreasing D_i and	then by increasing Γ_i
10:	allocBandwidth(\mathbb{J}', G)	

11: end procedure

can impact the CCTs of all other coflows scheduled afterward. Consequently, a natural extension of the SRTF policy is sorting the coflows by their Γ values and scheduling them in that order (MINIMIZECCTOFFLINE in Pseudocode 1). This requires solving O(N) instances of Optimization (1) during each scheduling round, which is activated by a coflow's arrival, completion, and WAN events. We schedule a coflow if all of its FlowGroups can be scheduled simultaneously.

Work Conservation If the WAN is still not fully utilized after scheduling all coflows that can be scheduled in their entirety, we run a max-min multi-commodity flow (MCF) formulation similar to [47] on a combination of coflows (prioritizing \mathbb{C}_{Failed}) to ensure work conservation and maximize WAN utilization (line 14,15 in Pseudocode 1).

3.1.3 From Offline to Online

So far, we have assumed that all coflows arrive together and are known a priori. However, in practice, coflows arrive over time as DAG dependencies are met. Additionally, WAN links can fail and its bandwidth can fluctuate. Scheduling coflows in the FIFO order [32, 34] is a simple solution, but it can result in head-of-line blocking [21, 33, 46]. Instead, preemption can minimize the average completion time [21, 33, 46].

Starvation-Free Preemption We allow coflows with smaller remaining completion time to preempt larger ones to avoid head-of-line blocking (Pseudocode 2). To avoid starvation issue that may arise with preemptive scheduling, we guarantee each coflow to receive some share of the network – specifically, α fraction of the WAN capacity is shared between preempted coflows (line 2 in Pseudocode 1). By default, $\alpha = 0.1$.

Scalable Online Scheduling In the online scenario, many events that trigger re-optimization may arrive at arbitrary time:

- 1. Coflow being submitted as dependencies are met;
- 2. FlowGroup finishes;
- 3. Coflow finishes because all its FlowGroups finished;
- WAN topology changes because of bandwidth fluctuations/failures.

Running the offline algorithm upon each event would cause

high complexity. Terra avoids this high complexity by categorizing the events, and only re-optimizing those FlowGroups that need update. For WAN bandwidth fluctuations, we consider $\rho = 25\%$ to be the threshold for significant bandwidth change that can cause a rescheduling, filtering out short-term fluctuations.

3.2 Extensions

Supporting Deadlines To provide guaranteed completion of a coflow C_i within its deadline (D_i) , Terra uses admission control. We admit a coflow, if it can meet its deadline without violating that of any other already-admitted coflow's deadline – i.e., if its deadline is not further from its minimum completion time (Γ_i) in the current WAN condition (line 7 in Pseudocode 2). Note that we use a relaxation factor η ($\eta > 1$) to mitigate the variability of WAN. However, when the bandwidth fluctuation is more than ($\eta - 1$), no deadlines can be guaranteed. An admitted coflow is never preempted.

Completing a coflow faster than its deadline has no benefit [33]. Hence, a known optimization is elongating its CCT until the deadline and sharing the remaining bandwidth with others. This can be done by scaling the $f^k(u, v)$ values by Γ_i/D_i . Supporting DAGs and Pipelined Workloads Many data analytics jobs form DAGs of computation stages with communication stages or coflows in between [4, 5, 26, 51, 78]. Job masters can submit requests for each coflow in a DAG independently to Terra as dependencies are met. Job masters can also submit a coflow with only some of its flows as soon as their dependencies are met, and then update the coflow to add more flows if more dependencies are satisfied. This is useful when the preceding computation tasks do not finish at the same time. In this case, Terra tries to finish all the submitted flows of the coflow together, eventually finishing all the flows together. Our evaluation shows that this simple strategy performs well (§6). Although it may be possible to perform DAG-aware optimizations [43, 44], we consider that to be a job master-specific decision and out of Terra's purview.

4 Terra: System Design

So far we have focused on designing a scalable algorithm for minimizing the average coflow completion time (§3). In this section, we discuss how to implement the solution in a scalable manner too. Furthermore, we consider how to make it robust to WAN variabilities. We start with an architectural overview of the whole system and then provide insights into designing individual components.

4.1 Architectural Overview

As shown in Figure 5, Terra has two primary components. A logically centralized *Terra controller* orchestrates all data transfers. In each datacenter, a set of *Terra agents* coordinate with the controller and transfer data on behalf of the jobs. Interactions between them can be summarized as follows:

1. Job master(s) submit coflows to the Terra controller using



Figure 5. Terra architecture. GDA jobs interact with Terra using a client library. Terra controller leverages an SD-WAN controller to make scheduling-routing co-optimization decisions that are enforced through Terra agents (only one agent is shown in figure).

the Terra API (§5.2). A job can submit multiple coflows as their dependencies are met.

- 2. The controller maintains an up-to-date, global view of the WAN and coflows. Given these information, it computes which jobs to schedule, which WAN paths to use, and at what rates data should be sent via specific paths (§3).
- 3. Finally, the controller sends path and rate information to corresponding Terra agents, which perform rate limiting across multiple paths (§5.1).

The entire process takes place in an online manner.

4.2 Why Use a Centralized Design?

In Terra, all scheduling and routing decisions are made by its centralized master. This is because *making such decisions without global knowledge can lead to arbitrarily worse performance*. Prior work [31] has already shown that when a coflow scheduler does not coordinate, the average coflow completion time for *n* coflows has an approximation ratio lower-bound of $\Omega(\sqrt{n}) - i.e.$, it keeps becoming worse with increasing *n*. Because Terra's problem formulation generalizes the datacenter coflow scheduling problem – specifically, instead of considering network bottlenecks only at the edge, we consider possible bottlenecks anywhere in the WAN – the worst-case lower-bound in this scenario is at least as bad. As such, we must have coordination among all the components of Terra over the entire WAN.

Naturally, Terra's centralized design brings scalability concerns to its design forefront both during its normal operations, where every arrival or departure of a coflow calls for rescheduling, and in the presence of uncertainties such as WAN bandwidth fluctuations and failures that also require rescheduling. Each rescheduling round requires a central computation, followed by the dissemination and enforcement of central decisions. We discussed the scalability aspects of the former in Section 3, and we discuss the latter in the following.

4.3 Scalability

Minimizing Scheduling Overhead Because Terra must consider routing, it cannot use existing topology-agnostic heuristics [31, 33]. However, the total number of flows in a GDA coflow adds significant time complexity to an integer linear program-based solution. Consequently, Terra leverages the FlowGroup abstraction [58] that allows us to remove the integral constraints, leading to a practical solution (§3). Each scheduling round takes O(100) milliseconds for topologies described in [47] and [53], and O(1) seconds for larger topologies with O(10) datacenters (§6.6). Given that many GDA jobs take several minutes to complete [71], Terra is not timeconstrained in decision making and dissemination. Finally, because most traffic come from large jobs [22, 23, 33, 71], Terra can allow sub-second coflows - i.e., only a few RTTs over the WAN - to proceed without any coordination. This is similar to how SD-WANs handle interactive services [47, 53].

Restricting the Number of Paths (*k*) As explained in prior work [47], running an unconstrained MCF instance may result in allocations that require many rules in switches. Constraining the number of paths for each FlowGroup can mitigate these issues, but it may lead to suboptimal overall WAN utilization. Although using 15 shortest paths between each pair of datacenters worked well in that prior work, it can vary between WANs and must be determined experimentally by the operator. Operators can set any (sets of) $f^k(u, v) = 0$ to enforce such constraints in Terra (§6.7). *k* also dictates how many connections Terra must maintain between agent pairs.

Minimizing Rule Updates in the WAN In the context of Terra, an additional challenge is minimizing expensive rule updates throughout the entire WAN caused by route changes [47]. Instead of setting up new rules for each flow [47], Terra maintains a set of single-path persistent flows between each datacenter pairs and sets up only one set of rules for each persistent flow. The controller sets up forwarding rules in the SD-WAN to enforce their paths. Directing a data transfer through a specific path is then simply reusing corresponding pre-established flows. To completely avoid expensive rule updates. Terra reuses persistent connections for each of the k paths between two datacenters and performs communication on behalf of the applications ($\S5.1$). WAN states change only when these flows are initialized or reestablished after failures. A collateral benefit of this approach is that Terra uses only a small number of rules in each switch – e.g., up to 168 in a switch for the SWAN [47] topology in our evaluation.

4.4 Robustness to Uncertainties

Failures of Terra agents do not permanently affect job executions because frameworks can fall back to default transfer mechanisms. States in Terra agents can be rebuilt upon restart when they contact the controller. Failure of the Terra controller is tied to that of the SDN controller. Its states can be rebuilt after all the Terra agents and job masters reconnect. Terra is robust to WAN events such as link or switch failures and large bandwidth fluctuations from background traffic, because it can observe and reschedule according to the latest WAN state. Upon such events, Terra updates its internal WAN representation, recomputes the set of viable paths between datacenter pairs, and updates corresponding schedules. The entire process takes a small fraction of a typical GDA job's duration (§6.5).

Because data transfers are decoupled from the jobs, we do not have to consider sender (Map) task failures. If a receiver is restarted in another machine of the same datacenter upon failure, Terra API supports updating destination(s) of a submitted coflow.

5 Implementation Details

We have implemented Terra in about 8000 lines of Java including integrations with the Floodlight [13] SDN controller and Apache YARN [3]. In this section, we discuss Terra's integration with the SD-WAN and existing GDA frameworks.

5.1 Integration with SD-WAN

WAN topologies have many redundant paths, and Terra utilizes them to minimize coflow completion times and maximize WAN utilization. Enforcing the multipath rate allocations of Terra's optimizer poses several practical challenges.

Multipath Data Transfers via Application-Layer Overlay The first challenge is emulating a multipath data transfer layer on top of single-path transport protocols such as TCP. Terra creates an application-layer overlay network over the WAN using persistent connections between agents. For each path between each agent pair, one or more persistent TCP connections are maintained. All data transfers happen over these pre-established connections. The controller establishes these routes throughout the WAN during an offline initialization phase. Then the TCP connections are reused over the entire runtime for multiple coflows.

Per-FlowGroup Rate Enforcement The second challenge is enforcing rate allocation for each FlowGroup. Terra maps a FlowGroup across multiple end-to-end TCP flows, each with a unique combination of a sending agent, a receiving agent, its sending rate, and the path. When a FlowGroup is scheduled to start, be preempted, or change rate, the controller informs its sending agents, which transmit data through pre-established connections for each path at designated rates.

Handling WAN Latency Heterogeneity Emulating multipath transmission over TCP flows brings a new challenge. Because of heterogeneous latencies between datacenter pairs, such multipath transmissions can incur many out-of-order data chunks on the receiver side. Terra buffers any out-oforder data to a block device and provides only in-order data to GDA jobs, mitigating this issue.

Supporting Other Transport Layer Our current implementation is based upon TCP. There is also a possible way forward

to implement Terra on top of MPTCP [67] by enforcing Terracalculated rates directly via MPTCP's subflow scheduler.

5.2 Integration with GDA Framework

Terra Interface Terra provides a simple API for job masters to submit new coflows, check their status, and update submitted coflows. A job master can submit a coflow transfer request with the set of its flows and an optional deadline, and it receives a unique CoflowId (-1 if the coflow has a deadline that cannot be met).

val cId = submitCoflow(Flows, [deadline])

Conversions from flows to FlowGroups as well as mapping of path allocations to pre-established TCP flows between datacenters happen internally.

The job master can check the status of a submitted coflow using its CoflowId.

val status = checkStatus(cId)

Finally, the job master can modify flows within a submitted coflow as well. Terra assumes that flows within a coflow are uniquely identifiable.

updateCoflow(cId, Flows)

Integration with Apache YARN Essentially, Terra substitutes the Shuffle Service of YARN. Terra master runs in the same datacenter as the Application Master of GDA jobs. When Map tasks finish, instead of a shuffle request, the Application Master submits a coflow request to the Terra controller. Terra informs the Application Master after the coflow has completely been transferred.

6 Evaluation

We evaluated Terra on 3 WAN topologies and 4 benchmarks/industrial workloads in testbed experiments and largescale simulations. Our key findings are as follows:

- In experiments, Terra improves the average JCT by 1.55– 3.43× on average and 2.12×–8.49× at the 95th percentile w.r.t. TCP while improving WAN utilization by 1.32×– 1.76× (§6.2).
- Extensive simulations show that Terra's average benefits across 12 <WAN topology, workload> combinations range from 1.04×-2.53× in the smallest topology and 1.52×-26.97× in the largest topology. 95th percentile improvements are similar (§6.3).
- Terra enables 2.82×-4.29× more coflows to meet their deadlines in our testbed experiments (§6.4).
- Terra is robust against failures (§6.5), its controller can scale to large topologies (§6.6), and it performs well under different parameter settings (§6.7).

6.1 Methodology

WAN Topologies We consider 3 inter-DC WANs.

1. SWAN [47, Figure 8]: Microsoft's inter-datacenter WAN with 5 datacenters and 7 inter-datacenter links. We calculate

link bandwidth using the setup described by Hong et al. [47].

2. *G-Scale* [53, Figure 1]: Google's inter-datacenter WAN with 12 datacenters and 19 inter-datacenter links.

3. ATT [6]: AT&T's MPLS backbone network in North America with 25 nodes and 56 links. We consider one datacenter connected to each node to create a topology larger than SWAN and G-Scale.

Given the locations, we use geographic distances as proxies for link latencies. Similar to Hong et al. [47], we estimate capacities for G-Scale and ATT using the gravity model [69]. Workloads We consider 4 workloads that consist of mix of jobs from public benchmarks – TPC-DS [15], TPC-H [16], and *BigBench* [7] – and from *Facebook* (*FB*) production traces [9, 14]. In each run for the benchmarks, jobs are randomly chosen from one of the corresponding benchmarks and follow an arrival distribution similar to that in production traces, because the benchmarks do not have arrival distributions. We vary the scale factor of the queries from 40 to 100, so each job lasts from few minutes to tens of minutes. Each benchmark experiment has 400 jobs, where job DAGs are generated by the Apache Calcite query optimizer [2] during execution by Tez [5]. The Facebook one has 526 simple MapReduce jobs. Input tables for jobs are placed across datacenters in a way that a single table can spread across at most $\frac{N}{2}$ + 1 out of N datacenters. Tasks run with datacenter locality.

Testbed Setup We built a testbed to emulate the SWAN topology [47] with 10 machines in each datacenter. Terra controller runs on a host inside the datacenter that minimizes the control message latency to all datacenters. Each datacenter has one switch, represented by a machine running one Open vSwitch instance. The switches are connected by VLANs, on top of a physical 40Gbps switch. We set the capacity of the links between switches to 1Gbps, to avoid saturating the physical switch. The bandwidth and latency constraints are enforced by Linux Traffic Control (tc).

Simulator We conducted large-scale evaluations using a flow-level simulator that has the same logic as in the actual Terra controller. The simulator assumes instant communication between Terra components.

Baselines We compare Terra against five baselines:

- 1. *Per-Flow Fairness*: An ideal, single-path per-flow fairness scheduler. Flows follow fixed routes calculated by the controller. We use TCP in experiments.
- 2. Multipath: An ideal multipath extension to Per-Flow.
- 3. SWAN-MCF: WAN optimizer proposed in [47].
- 4. Varys: Coflow scheduler proposed in [33].
- 5. *Rapier*: Coflow scheduling-routing solution for datacenters proposed in [83]. We choose $\delta = 20$, because it performed the best among values from $\delta = 5$ to $\delta = 100$.

Metrics Our primary metric to quantify performance is the improvement in the *average JCT* computed as:

Factor of Improvement = $\frac{\text{Duration of an Approach}}{\text{Duration of Terra}}$



Figure 6. [Testbed] Factors of Improvement of JCT and CCT using Terra w.r.t. Per-Flow for different workloads on SWAN.

Factor of Improvement (FoI) greater than 1 means Terra is performing better, and vice versa.

We use FoI in *average WAN utilization* across the entire WAN (calculated using the same method as above) to compare the efficiency of the compared solutions.

For deadline-sensitive coflows, the primary metric is the percentage of coflows that meet their deadlines.

We use k = 15 and $\alpha = 0.1$ as defaults.

6.2 Terra's Performance in Testbed Experiments

We evaluated Terra on our testbed for SWAN topology to examine its impact on JCT and WAN utilization. We evaluate G-Scale and ATT topologies using simulation in Section 6.3.

6.2.1 Impact on JCT

Figure 6a shows that Terra improves the average JCT by at least 1.55× in comparison to Per-Flow (i.e., single-path, fixed-route TCP). At the 95th percentile, the factor of improvement is at least 2.12×. Note that these numbers include the overheads of schedule computation, preemption, and rescheduling messages from the controller. Figure 6b shows the improvements in the average CCT, which does not include computation time and are noticeably higher. Figure 7 presents the CDFs of JCTs for all jobs in all 4 workloads.

We observe that the FB workload exhibits a different improvement factor than others. This is because the FB trace [9] has heavily skewed distributions – most jobs have little to no traffic, while a few have most of the tasks and account for almost all the volume. This is consistent with prior observations [33]. Because of heavy skews in both the number of flows and flow sizes, scheduling and multipath routing enabled by Terra provide even bigger benefits than that observed by Chowdhury et al. [33] for a longer version of the same trace. At the same time, however, Figure 7d shows that Terra does not perform well when scheduling sub-second jobs; we advise not to centrally schedule such small jobs.

6.2.2 Impact on WAN Utilization

As is shown in Table 2, Terra improves the WAN utilization by at least $1.32 \times$ by effectively using multiple paths.

6.3 Terra in Trace-Driven Simulations

So far we have compared Terra only to single-path, fixed-route TCP. A natural question is whether Terra's improvements are



Figure 7. [Testbed] JCTs of individual jobs using Terra and Per-Flow for different workloads on the SWAN topology.

Workload	BigBench	TPC-DS	TPC-H	FB
FoI	1.76	1.49	1.32	1.64

Table 2. [Testbed] WAN utilization FoI of Terra w.r.t. Per-Flow.

mostly due to scheduling coflows or from multipath routing. Here, we extend our evaluation to simulate and compare Terra across all 12 <topology, workload> combinations against five baselines that focus on either scheduling or routing. We assume 100 machines per datacenter in these cases.

6.3.1 Impact on JCT

Table 3 shows that Terra improves the average JCT by $1.04 \times -2.53 \times$ in SWAN, $1.80 \times -16.63 \times$ in G-Scale and $1.52 \times -26.97 \times$ in ATT with similar 95th percentile improvements. Although we omit detailed CDFs for brevity, Terra outperforms its counterparts in varying degrees across all percentiles except for the shaded cells in Table 3.

Which Jobs See the Biggest Benefits? We calculated the Pearson's correlation coefficients (r) between FoIs w.r.t. the baseline and total WAN transfers for all 12 <topology, workload> combinations. The result showed consistent negative correlations (-0.05 to -0.39) across the board, suggesting that smaller jobs see more benefits than the bigger ones.

How does Topology or Workload Affect? There were no significant correlations between Terra's improvements and workloads, except for FB that showed a lower improvement for average JCT than that at the 95th percentile. This is again likely due to its heavy-tailed distribution. The large number of small jobs receive little benefit due to coordination overheads, resulting in lower improvement on average. Speedups from Terra for larger jobs contribute to the 95th percentile.

Performances of Terra and all baselines do vary across topologies. Terra performs increasingly better in larger topologies (i.e., G-Scale and ATT). In these cases, Multipath comes the closest to Terra because it leverages many available paths between datacenters. For the SWAN topology, Varys is the closest to Terra because there are not many available paths (only 5 nodes and 7 links). Overall, Terra outperforms the rest via joint scheduling-routing co-optimization.

How Far are We From the Optimal? Calculating the optimal solution of a computationally intractable problem is infeasible. Instead, we use slowdowns of coflows as a loose



Figure 8. Percentage of coflows that meet deadline w.r.t the baselines for deadlines set to $d \times of$ a coflow's minimum CCT.

lower bound. We calculated slowdown of a coflow by comparing the completion time using Terra with its minimum (i.e., in an empty network). We found that the average slowdown using Terra was between $1.08 \times$ and $2.95 \times$ across all 12 <topology, workload> combinations. In contrast, the baselines ranged between $1.77 \times$ and $82.18 \times$.

6.3.2 Impact on WAN Utilization

Table 4 shows the improvements in WAN utilization using Terra w.r.t. the best of all five baselines in terms of utilization for all <topology, workload> combinations. Terra achieved 1.06× to 1.76× higher utilization for all combinations except <SWAN, FB>.

6.4 Performance on Deadline-Sensitive Coflows

For deadline-constrained experiments, we set the deadline of a coflow to be $d \times$ its minimum completion time (i.e., in an empty network) and vary *d* from 2 to 6. We run experiments for BigBench and SWAN in both Testbed and simulation.

Testbed Experiments Figure 8a shows that Terra allowed $2.82 \times$ to $4.29 \times$ more coflows to complete within deadlines compared to Per-Flow. Note that a small fraction of the admitted coflows missed their deadlines. This is due to the uncertainty of the global state at the controller in between feedback loops. However, most of them still completed within 50% of their deadline.

Trace-driven Simulations Figure 8b shows that Terra allowed $1.07 \times$ to $2.31 \times$ more coflows to complete within deadlines compared to all the baselines in simulations. Here, all admitted coflows completed in Terra because we assume instantaneous communication between the controller and agents.

	Topology	SWAN			G-Scale			ATT					
	Workload	BB	FB	TPC-DS	TPC-H	BB	FB	TPC-DS	TPC-H	BB	FB	TPC-DS	TPC-H
Per-Flow	Avg.	1.78	1.96	2.16	2.53	9.79	8.08	12.45	16.63	8.64	4.50	8.98	9.57
	95%-tile	1.57	10.04	1.63	1.65	8.82	86.29	13.40	11.93	10.61	74.66	7.41	7.15
Varue	Avg.	1.15	1.04	1.16	1.68	6.46	3.87	8.03	16.32	10.05	2.79	11.44	26.97
varys	95%-tile	1.02	1.67	1.01	1.81	5.08	2.73	13.24	25.17	11.04	5.25	12.86	30.94
SWAN-MCF	Avg.	1.59	1.69	1.73	2.17	6.13	4.26	8.81	12.60	6.64	2.64	7.11	7.83
	95%-tile	1.28	8.80	1.27	1.34	4.98	42.85	9.40	9.04	7.18	38.49	5.34	5.29
Multipath	Avg.	1.30	1.65	1.25	1.28	2.77	4.11	2.88	3.24	3.75	2.48	3.03	2.82
	95%-tile	1.15	7.66	0.90	0.86	2.49	40.99	3.51	2.96	5.24	34.86	2.32	2.26
Rapier	Avg.	1.67	2.15	1.32	2.09	1.80	1.91	1.81	1.80	2.37	1.90	1.73	1.52
	95%-tile	1.64	2.70	1.25	1.57	1.63	5.72	1.60	1.88	2.64	4.23	1.55	1.42

Table 3. [Simulation] Factors of improvement in the average and 95th percentile JCT using Terra w.r.t. baselines.

Workload	BigBench	TPC-DS	TPC-H	FB
SWAN	1.12	1.14	1.06	0.92
G-Scale	1.22	1.14	1.09	1.12
ATT	1.42	1.34	1.76	1.38

Table 4. [Simulation] WAN utilization FoI of Terra.



Figure 9. [Testbed] An example of failure handling. FlowGroup of Job 1 is denoted by the blue (dark) arrows, FlowGroup of Job 2 is denoted by orange (light) arrows. The dashed line with a cross denotes the failed link. (b): Link failed, Job 2 got preempted. (c): Job 1 finished, Job 2 got rescheduled. (d): Link recovered, Job 2 received a new path.



Figure 10. [Testbed] Throughput of jobs and the failed link.

6.5 Reactive Re-Optimization Upon Failure

We evaluate Terra's robustness upon failure by a case study in our testbed. Figure 9 shows an example where one link (LA-NY) failed when there are two jobs {Job 1, Job 2} running, and Figure 10 shows the throughput change throughout this process. Note that we set $\alpha = 0$ for ease of exposition.

In this case, Job 1 has a smaller volume and thus higher priority than Job 2. Terra reacts to the link failure within 10 seconds and preempts Job 2 (Figure 9b), minimizing the impact of link failure to Job 1's throughput. After the completion of Job 1, Terra re-schedules Job 2 (Figure 9c). Finally, when the failed link is reinstated (Figure 9d), Terra adds a new path for Job 2.



Figure 11. Scheduling overhead of Terra against Rapier.

6.6 Terra Overheads

Computational Complexity In our experiments, we ran Terra controller on a machine with two 2.6GHz Intel Xeon Gold 6142 CPU and measured the number of LP computations and total time spent for each scheduling decision. For BigBench on SWAN topology, for each schedule, Terra needs to solve 28.4 LPs on average, taking 74.43 ms. For the same workload on ATT topology, each schedules takes 589.1 ms to solve 31.46 LPs on average (2.991 s to solve 52 LPs at the 95th percentile). Given that many job lasts for a few minutes, this overhead is acceptable in most cases.

We also compared Terra against Rapier, as shown in Figure 11. For Rapier optimizing BigBench on SWAN topology, each scheduling round takes 1.952 seconds to solve 36.5 LPs, which is $26.2 \times$ worse than Terra. For a larger topology (G-Scale), Rapier is even worse (29.14 \times). This is because FlowGroups reduce the number of flows by up to $100 \times$ when geo-distributed tasks are spread across 10 hosts in each datacenter.

Number of Rules and Rule Updates Terra incurs rule setup cost upon starting and in case of failures. Terra installs only up to 168 flow rules in each switch for the SWAN topology. Operators can vary k to limit the number of rules per switch.

6.7 Sensitivity Analysis

Impact of Restricting Paths Terra minimizes the number of rules it has to install by reusing existing TCP connections across multiple end-to-end paths between two datacenters. However, if the number of possible paths between them (k)increases, Terra has to establish and maintain more TCP connections. Consequently, Terra allows operators to restrict the number of possible paths between datacenters (§3.1.1). Figure 12 shows the impact of k for the all workloads on the



Figure 12. [Simulation] Improvements in the average JCT and utilization using Terra w.r.t. Per-Flow on ATT topology as the number of paths between two datacenters (k) is varied.



Figure 13. [Testbed] Factor of Improvement in the average JCT for workloads with scaled arrival rates in the SWAN topology.



Figure 14. [Testbed] Improvements in the average JCT using Terra w.r.t. Per-Flow on the SWAN topology with increasing number of machines in each datacenter.

ATT topology. We observe that: (i) With larger k, Terra's improvements become higher. This is because larger k allows for more multipath benefits. (ii) After k reached a threshold (it is between k = 5 and k = 10 for ATT), increasing k does not significantly affect JCT or utilization.

Impact of Job Arrival Rate and Load We scaled the arrival rate of the queries to increase load and evaluated Terra's performance in testbed. Figure 13 shows that Terra performs better with increasing arrival rate – i.e., with increasing load. When the network is lightly loaded, the room for performance improvement is lower. Increasing load by making jobs larger (instead of making jobs arrive in shorter intervals) also resulted in increasing benefits.

Computation v.s. Communication By keeping the time spent in communication constant, we vary the number of machines in each datacenter and estimate the average JCT. Figure 14 shows improvements of average JCTs w.r.t. the number of machines used for all jobs on SWAN topology. Because JCT = $(T_{\text{Comm}} + T_{\text{Comp}})$ for each stage, the improvements increase with the number of machines used.

Choice of α We also compared $\alpha = 0.2$ and $\alpha = 0.1$ for BigBench on the SWAN topology and found that the average JCT is 2.3% higher for $\alpha = 0.2$.

7 Related Work

Geo-Distributed Analytics Existing geo-distributed analytics solutions focus on two goals: minimizing WAN usage and minimizing the average JCT via query planning and/or data placement [48–50, 65, 66, 71–73]. However, they all ignore the WAN topology and are not robust to WAN events. In contrast, Terra focuses on simultaneously scheduling and routing WAN coflows and can complement existing solutions.

Speeding up Data Analytics Efforts in speeding up data analytics include scheduling [25, 40, 42, 43, 45, 52, 79], caching [23, 60, 68, 78], query planning [2, 26, 76], straggler mitigation [22, 25, 70, 77], approximation [17, 24], and data placement [29, 35, 39, 63]. The primary context along these directions is a single datacenter, whereas Terra focuses on optimizing performance across multiple datacenters, where WAN bandwidth is often the primary bottleneck.

Flow and Coflow Scheduling Flow scheduling [19–21, 27, 46, 80] and coflow scheduling [18, 31–33, 82] deal with optimizing communication performance in datacenters. The former is application-agnostic, while the latter is applicationaware but assumes full bisection bandwidth datacenter networks. Similar to them, Terra can account for minimizing completion times as well as meeting deadlines; unlike them, Terra is both topology- and application-aware.

Rapier [83] comes the closest to Terra in that it also considers routing alongside scheduling to handle datacenter topologies. In contrast, Terra considers general WAN topologies. Furthermore, Rapier uses single-path routing, does not use Terra's FlowGroup optimization, relies on time-division multiplexing (using its δ parameter) to avoid starvation, and updates switch rules on every reschedule – all of which contribute to its lower performance and higher complexity (§6.3).

Siphon [62] is a WAN-agnostic framework minimizing CCT for GDA jobs. Although it applies similar ideas of creating a overlay network and multipath transfers on that overlay, it is agnostic to the underlying WAN. As such, it does not consider WAN routing and cannot directly react to WAN uncertainties.

WAN Traffic Engineering Traditionally, optimizing WAN transfers revolved around tuning (ECMP and/or OSPF) weights [37, 38] and adapting allocations across preestablished tunnels [56, 74], often via MPLS [75]. With the advent of SDNs, Google [53, 58] and Microsoft [47] have shown that it is indeed possible to perform traffic engineering in a (logically) centralized manner. Terra builds on top and extends the latter works. Another relevant body of work is WAN data transfers with deadlines. However, unlike these point-to-point [54, 55, 57–59, 81] or point-to-multipoint [64] solutions, Terra leverages application-level semantics to optimize multipoint-to-multipoint coflows.

8 Conclusion

Despite growing interests in geo-distributed analytics and SD-WANs, there exists a large gap between the two emerging areas. The former ignores the WAN, while the latter ignores readily available application-level semantics, leading to large performance loss. Terra bridges this gap by enabling scheduling-routing co-optimization in geo-distributed analytics via SDN-based WAN traffic engineering. It uses coflows to schedule WAN transfers from geo-distributed jobs, and leverages FlowGroups and SDN to compute and dictate their routes across multiple paths. Integrations with the FloodLight SDN controller and Apache YARN, and evaluation on 12 <topology, workload> combinations show that co-optimization can improve the average JCT by $1.55 \times -3.43 \times$ on average while moderately improving the average WAN utilization and complete 2.82×-4.29× more coflows within their deadlines. Furthermore, Terra enables geo-distributed jobs to dynamically react to large bandwidth fluctuations due to failures in the WAN and traffic variabilities.

In conclusion, this paper is only a first step in bringing WAN into the picture of geo-distributed analytics. It opens up several exciting research problems, which include cooptimizing without knowing the WAN topology (e.g., when running in the cloud environment), without knowing the traffic matrices (e.g., geo-distributed streaming), and extending to streaming analytics.

References

- [1] [n. d.]. Amazon datacenter locations. https://aws.amazon.com/ about-aws/global-infrastructure/.
- [2] [n. d.]. Apache Calcite. https://calcite.apache.org.
- [3] [n. d.]. Apache Hadoop NextGen MapReduce (YARN). http://goo.gl/ etTGA.
- [4] [n. d.]. Apache Hive. http://hive.apache.org.
- [5] [n. d.]. Apache Tez. http://tez.apache.org.
- [6] [n. d.]. AT&T MPLS Backbone. http://www.topology-zoo.org/ dataset.html.
- [7] [n. d.]. Big-Data-Benchmark-for-Big-Bench. https://github.com/ intel-hadoop/Big-Data-Benchmark-for-Big-Bench.
- [8] [n. d.]. Cisco Internet of Everything WhitePaper. http://ioeassessment.cisco.com/learn/ 2015-ioe-value-index-whitepaper.
- [9] [n. d.]. Coflow Benchmark Based on Facebook Traces. https://github. com/coflow/coflow-benchmark.
- [10] [n. d.]. Google datacenter locations. http://www.google.com/about/ datacenters/inside/locations/.
- [11] [n. d.]. Internet Users. http://www.internetlivestats.com.
- [12] [n. d.]. Microsoft datacenter locations. http://www.microsoft.com/ en-us/server-cloud/cloud-os/global-datacenters.aspx.
- [13] [n. d.]. Project Floodlight. http://www.projectfloodlight.org/ floodlight.
- [14] [n. d.]. Statistical Workload Injector for MapReduce (SWIM). https: //github.com/SWIMProjectUCB/SWIM.
- [15] [n. d.]. TPC Benchmark DS (TPC-DS). http://www.tpc.org/tpcds.
- [16] [n. d.]. TPC Benchmark H (TPC-H). http://www.tpc.org/tpch.
- [17] Sameer Agarwal, Barzan Mozafari, Aurojit Panda, Henry Milner, Samuel Madden, and Ion Stoica. 2013. BlinkDB: Queries with bounded errors and bounded response times on very large data. In *EuroSys*.

- [18] Saksham Agarwal, Shijin Rajakrishnan, Akshay Narayan, Rachit Agarwal, David Shmoys, and Amin Vahdat. 2018. Sincronia: near-optimal network design for coflows. In SIGCOMM.
- [19] Mohammad Al-Fares, Sivasankar Radhakrishnan, Barath Raghavan, Nelson Huang, and Amin Vahdat. 2010. Hedera: Dynamic flow scheduling for data center networks. In NSDI.
- [20] Mohammad Alizadeh, Albert Greenberg, David A Maltz, Jitendra Padhye, Parveen Patel, Balaji Prabhakar, Sudipta Sengupta, and Murari Sridharan. 2010. Data Center TCP (DCTCP). *SIGCOMM* (2010).
- [21] Mohammad Alizadeh, Shuang Yang, Milad Sharif, Sachin Katti, Nick Mckeown, Balaji Prabhakar, and Scott Shenker. 2013. pFabric: Minimal Near-Optimal Datacenter Transport. In SIGCOMM.
- [22] G. Ananthanarayanan, A. Ghodsi, Scott Shenker, and Ion Stoica. 2013. Effective Straggler Mitigation: Attack of the Clones. In NSDI.
- [23] G. Ananthanarayanan, A. Ghodsi, A. Wang, D. Borthakur, S. Kandula, S. Shenker, and I. Stoica. 2012. PACMan: Coordinated Memory Caching for Parallel Jobs. In *NSDI*.
- [24] Ganesh Ananthanarayanan, Michael Chien-Chun Hung, Xiaoqi Ren, Ion Stoica, Adam Wierman, and Minlan Yu. 2014. GRASS: Trimming stragglers in approximation analytics. In NSDI.
- [25] G. Ananthanarayanan, S. Kandula, A. Greenberg, I. Stoica, Y. Lu, B. Saha, and E. Harris. 2010. Reining in the Outliers in MapReduce Clusters using Mantri. In OSDI.
- [26] Michael Armbrust, Reynold S Xin, Cheng Lian, Yin Huai, Davies Liu, Joseph K Bradley, Xiangrui Meng, Tomer Kaftan, Michael J Franklin, Ali Ghodsi, and Matei Zaharia. 2015. Spark SQL: Relational data processing in Spark. In SIGMOD.
- [27] Wei Bai, Li Chen, Kai Chen, Dongsu Han, Chen Tian, and Hao Wang. 2015. Information-Agnostic Flow Scheduling for Commodity Data Centers. In NSDI.
- [28] Matt Calder, Xun Fan, Zi Hu, Ethan Katz-Bassett, John Heidemann, and Ramesh Govindan. 2013. Mapping the expansion of Google's serving infrastructure. In *IMC*.
- [29] Mosharaf Chowdhury, Srikanth Kandula, and Ion Stoica. 2013. Leveraging Endpoint Flexibility in Data-Intensive Clusters. In SIGCOMM.
- [30] Mosharaf Chowdhury and Ion Stoica. 2012. Coflow: A Networking Abstraction for Cluster Applications. In *HotNets*.
- [31] Mosharaf Chowdhury and Ion Stoica. 2015. Efficient Coflow Scheduling Without Prior Knowledge. In SIGCOMM.
- [32] Mosharaf Chowdhury, Matei Zaharia, Justin Ma, Michael I. Jordan, and Ion Stoica. 2011. Managing Data Transfers in Computer Clusters with Orchestra. In SIGCOMM.
- [33] Mosharaf Chowdhury, Yuan Zhong, and Ion Stoica. 2014. Efficient Coflow Scheduling with Varys. In SIGCOMM.
- [34] Fahad Dogar, Thomas Karagiannis, Hitesh Ballani, and Ant Rowstron. 2014. Decentralized Task-Aware Scheduling for Data Center Networks. In SIGCOMM.
- [35] Mohamed Y. Eltabakh, Yuanyuan Tian, Fatma Özcan, Rainer Gemulla, Aljoscha Krettek, and John McPherson. 2011. CoHadoop: Flexible Data Placement and Its Exploitation in Hadoop. In VLDB.
- [36] Alan Ford, Costin Raiciu, Mark J. Handley, and Olivier Bonaventure. 2013. TCP Extensions for Multipath Operation with Multiple Addresses. RFC 6824. https://doi.org/10.17487/rfc6824
- [37] Bernard Fortz, Jennifer Rexford, and Mikkel Thorup. 2002. Traffic engineering with traditional IP routing protocols. *IEEE Communications Magazine* 40, 10 (2002), 118–124.
- [38] Bernard Fortz and Mikkel Thorup. 2000. Internet traffic engineering by optimizing OSPF weights. In *INFOCOM*.
- [39] Sanjay Ghemawat, Howard Gobioff, and Shun-Tak Leung. 2003. The Google File System. In SOSP.
- [40] Ali Ghodsi, Matei Zaharia, Benjamin Hindman, Andy Konwinski, Scott Shenker, and Ion Stoica. 2011. Dominant Resource Fairness: Fair Allocation of Multiple Resource Types.. In NSDI.
- [41] Joseph E Gonzalez, Reynold S Xin, Ankur Dave, Daniel Crankshaw,

Michael J Franklin, and Ion Stoica. 2014. GraphX: Graph processing in a distributed dataflow framework. In *OSDI*.

- [42] Robert Grandl, Ganesh Ananthanarayanan, Srikanth Kandula, Sriram Rao, and Aditya Akella. 2014. Multi-Resource Packing for Cluster Schedulers. In SIGCOMM.
- [43] Robert Grandl, Mosharaf Chowdhury, Aditya Akella, and Ganesh Ananthanarayanan. 2016. Altruistic Scheduling in Multi-Resource Clusters. In OSDI.
- [44] Robert Grandl, Srikanth Kandula, Sriram Rao, Aditya Akella, and Janardhan Kulkarni. 2016. Graphene: Packing and dependency-aware scheduling for data-parallel clusters. In =OSDI.
- [45] B. Hindman, A. Konwinski, M. Zaharia, A. Ghodsi, A.D. Joseph, R. Katz, S. Shenker, and I. Stoica. 2011. Mesos: A Platform for Fine-Grained Resource Sharing in the Data Center. In *NSDI*.
- [46] Chi-Yao Hong, Matthew Caesar, and P. Brighten Godfrey. 2012. Finishing Flows Quickly with Preemptive Scheduling. In SIGCOMM.
- [47] Chi-Yao Hong, Srikanth Kandula, Ratul Mahajan, Ming Zhang, Vijay Gill, Mohan Nanduri, and Roger Wattenhofer. 2013. Achieving high utilization with software-driven WAN. In *SIGCOMM*.
- [48] K. Hsieh, A. Harlap, N. Vijaykumar, D. Konomis, G. Ganger, P. Gibbons, and O. Mutlu. 2017. Gaia: Geo-Distributed Machine Learning Approaching LAN Speeds. In *NSDI*.
- [49] Chien-Chun Hung, Ganesh Ananthanarayanan, Leana Golubchik, Minlan Yu, and Mingyang Zhang. 2018. Wide-area Analytics with Multiple Resources. In *EuroSys*.
- [50] Chien-Chun Hung, Leana Golubchik, and Minlan Yu. 2015. Scheduling Jobs Across Geo-Distributed Datacenters. In SoCC.
- [51] Michael Isard, Mihai Budiu, Yuan Yu, Andrew Birrell, and Dennis Fetterly. 2007. Dryad: Distributed Data-Parallel Programs from Sequential Building Blocks. In *EuroSys*.
- [52] Michael Isard, Vijayan Prabhakaran, Jon Currey, Udi Wieder, Kunal Talwar, and Andrew Goldberg. 2009. Quincy: Fair Scheduling for Distributed Computing Clusters. In SOSP.
- [53] Sushant Jain, Alok Kumar, Subhasree Mandal, Joon Ong, Leon Poutievski, Arjun Singh, Subbaiah Venkata, Jim Wanderer, Junlan Zhou, Min Zhu, J. Zolla, U. Hölzle, S. Stuart, and A. Vahdat. 2013. B4: Experience with a globally-deployed software defined WAN. In *SIGCOMM*.
- [54] Virajith Jalaparti, Ivan Bliznets, Srikanth Kandula, Brendan Lucier, and Ishai Menache. 2016. Dynamic Pricing and Traffic Engineering for Timely Inter-Datacenter Transfers. In SIGCOMM.
- [55] Xin Jin, Yiran Li, Da Wei, Siming Li, Jie Gao, Lei Xu, Guangzhi Li, Wei Xu, and Jennifer Rexford. 2016. Optimizing bulk transfers with software-defined optical WAN. In *SIGCOMM*.
- [56] Srikanth Kandula, Dina Katabi, Bruce Davie, and Anna Charny. 2005. Walking the tightrope: Responsive yet stable traffic engineering. In *SIGCOMM.*
- [57] Srikanth Kandula, Ishai Menache, Roy Schwartz, and Spandana Raj Babbula. 2015. Calendaring for wide area networks. In SIGCOMM.
- [58] Alok Kumar, Sushant Jain, Uday Naik, Anand Raghuraman, Nikhil Kasinadhuni, Enrique Cauich Zermeno, C Stephen Gunn, Jing Ai, Björn Carlin, Mihai Amarandei-Stavila, M. Robin, A. Siganporia, S. Stuart, and A. Vahdat. 2015. BwE: Flexible, hierarchical bandwidth allocation for WAN distributed computing. In *SIGCOMM*.
- [59] Nikolaos Laoutaris, Michael Sirivianos, Xiaoyuan Yang, and Pablo Rodriguez. 2011. Inter-datacenter bulk transfers with NetStitcher. In SIGCOMM.
- [60] Haoyuan Li, Ali Ghodsi, Matei Zaharia, Scott Shenker, and Ion Stoica. 2014. Tachyon: Reliable, memory speed storage for cluster computing frameworks. In *SoCC*.
- [61] Yupeng Li, Shaofeng H-C Jiang, Haisheng Tan, Chenzi Zhang, Guihai Chen, Jipeng Zhou, and Francis Lau. 2016. Efficient online coflow routing and scheduling. In *MobiHoc*.
- [62] S Liu, L Chen, and B Li. 2018. Siphon: Expediting Inter-Datacenter

Coflows in Wide-Area Data Analytics. In USENIX ATC.

- [63] Ed Nightingale, Jeremy Elson, Owen Hofmann, Yutaka Suzue, Jinliang Fan, and Jon Howell. 2012. Flat Datacenter Storage. In OSDI.
- [64] Mohammad Noormohammadpour, Cauligi S Raghavendra, Sriram Rao, and Srikanth Kandula. 2017. DCCast: Efficient Point to Multipoint Transfers Across Datacenters. In *HotCloud*.
- [65] Qifan Pu, Ganesh Ananthanarayanan, Peter Bodik, Srikanth Kandula, Aditya Akella, Victor Bahl, and Ion Stoica. 2015. Low Latency Geodistributed Data Analytics. In SIGCOMM.
- [66] Ariel Rabkin, Matvey Arye, Siddhartha Sen, Vivek S Pai, and Michael J Freedman. 2014. Aggregation and degradation in JetStream: Streaming analytics in the wide area. In NSDI.
- [67] Costin Raiciu, Sebastien Barre, Christopher Pluntke, Adam Greenhalgh, Damon Wischik, and Mark Handley. 2011. Improving datacenter performance and robustness with multipath TCP. In ACM SIGCOMM Computer Communication Review, Vol. 41. 266–277.
- [68] KV Rashmi, Mosharaf Chowdhury, Jack Kosaian, Ion Stoica, and Kannan Ramchandran. 2016. EC-Cache: Load-Balanced, Low-Latency Cluster Caching with Online Erasure Coding. In OSDI.
- [69] Matthew Roughan, Albert Greenberg, Charles Kalmanek, Michael Rumsewicz, Jennifer Yates, and Yin Zhang. 2002. Experience in measuring backbone traffic variability: Models, metrics, measurements and meaning. In *INM*.
- [70] Shivaram Venkataraman, Aurojit Panda, Ganesh Ananthanarayanan, Michael J Franklin, and Ion Stoica. 2014. The power of choice in data-aware cluster scheduling. In OSDI.
- [71] Raajay Viswanathan, Ganesh Ananthanarayanan, and Aditya Akella. 2016. Clarinet: WAN-aware optimization for analytics queries. In OSDI.
- [72] Ashish Vulimiri, Carlo Curino, B Godfrey, J Padhye, and G Varghese. 2015. Global analytics in the face of bandwidth and regulatory constraints. In *NSDI*.
- [73] Hao Wang and Baochun Li. 2017. Lube: Mitigating Bottlenecks in Wide Area Data Analytics. In *HotCloud*.
- [74] Hao Wang, Haiyong Xie, Lili Qiu, Yang Richard Yang, Yin Zhang, and Albert Greenberg. 2006. COPE: Traffic engineering in dynamic networks. In SIGCOMM.
- [75] Xipeng Xiao, Alan Hannan, Brook Bailey, and Lionel M Ni. 2000. Traffic Engineering with MPLS in the Internet. *IEEE network* 14, 2 (2000), 28–33.
- [76] Reynold S Xin, Josh Rosen, Matei Zaharia, Michael J Franklin, Scott Shenker, and Ion Stoica. 2013. Shark: SQL and rich analytics at scale. In SIGMOD.
- [77] Matei Zaharia, Dhruba Borthakur, Joydeep Sen Sarma, Khaled Elmeleegy, Scott Shenker, and Ion Stoica. 2010. Delay Scheduling: A Simple Technique for Achieving Locality and Fairness in Cluster Scheduling. In *EuroSys*.
- [78] M. Zaharia, M. Chowdhury, T. Das, A. Dave, J. Ma, M. McCauley, M.J. Franklin, S. Shenker, and I. Stoica. 2012. Resilient Distributed Datasets: A Fault-Tolerant Abstraction for In-Memory Cluster Computing. In *NSDI*.
- [79] Matei Zaharia, Andy Konwinski, Anthony D. Joseph, Randy Katz, and Ion Stoica. 2008. Improving MapReduce Performance in Heterogeneous Environments. In OSDI.
- [80] David Zats, Tathagata Das, Prashanth Mohan, Dhruba Borthakur, and Randy Katz. 2012. DeTail: Reducing the Flow Completion Time Tail in Datacenter Networks. In SIGCOMM.
- [81] Hong Zhang, Kai Chen, Wei Bai, Dongsu Han, Chen Tian, Hao Wang, Haibing Guan, and Ming Zhang. 2015. Guaranteeing deadlines for inter-datacenter transfers. In *EuroSys*.
- [82] H. Zhang, L. Chen, B. Yi, K. Chen, M. Chowdhury, and Y. Geng. 2016. CODA: Toward Automatically Identifying and Scheduling COflows in the DArk. In *SIGCOMM*.
- [83] Yangming Zhao, Kai Chen, Wei Bai, Minlan Yu, Chen Tian, Yanhui

Geng, Yiming Zhang, Dan Li, and Sheng Wang. 2015. Rapier: Integrating Routing and Scheduling for Coflow-aware Data Center Networks. In *INFOCOM*.